METAPACE

Metapace S-62 – Competitively Priced Imager

www.metapace.com

Highlights

- Multi-faceted 2D area imager at a great price
- Captures all common 1D, 2D, postal and stacked codes
- Versatile: handheld and presentation modes
- Scan confirmation via green LED and beeper
- Simple connection via USB

Technical specifications

Scanner properties	
Type	2D imager
Light source	Lighting: white LED; aiming: red LED, 617 nm
Movement tolerance	100 mm/s, 13 mils UPC
Print contrast	Min. 35 % reflectance difference
Scanning angle	Rotation: ± 180°; pitch: ± 65°; skew: ± 60°
Supported barcodes	Standard 1D and 2D codes
Electronics	
Laser rating	EN class B; IEC62471
Voltage	5 V ± 5 % @ 400 mA
Interfaces	
I/F ports	USB
Specifics	
Impact resistance	Resists multiple 1 m drops to concrete
Protection rating	IP40
Environment	
Operating temperature	0 °C to 40 °C
Storage temperature	-40 °C to 60 °C
Humidity	5 % to 95 % RH (non-condensing)
Housing	
Dimensions (WxHxD)	95 x 68 x 152 mm
Weight	125 g (without cable)
Colour	Black
Warranty	
Period	60 month

S-62

METAPACE